

TECHNICKÉ PARAMETRE:

TYP	kód	U výstupné I _{out} = 0 mA	U výstupné pri I _{out} = ... mA
12WZS 5/800	B 317-X-X	5V DC ± 5%	I _{out} = 800mA 5V DC ± 5%
12WZS 9/800	B 318-X-X	9V DC ± 5%	I _{out} = 800mA 9V DC ± 5%
12WZS 12/800	B 319-X-X	12V DC ± 5%	I _{out} = 800mA 12V DC ± 5%

Vstupné napätie 230V/50Hz

Prevádzková teplota 0÷40 °C

Krytie IP 30

Hmotnosť 690g

Farba krabičky čierna, biela




š	v	d
71	57	107

Napájacie konektory:



Polarita:



C-5,50x2,10mm

D-5,50x2,50mm

F-5,50x1,50mm

I-5,50x2,10mm

J-5,50x2,50mm

K-5,50x1,50mm

TECHNICKÉ PARAMETRE:

TYP	kód	U výstupné I _{out} = 0 mA	U výstupné pri I _{out} = ... mA
12WZS 15/500	B 320-X-X	15V DC ± 5%	I _{out} = 500mA 15V DC ± 5%
12WZS 18/500	B 321-X-X	18V DC ± 5%	I _{out} = 500mA 18V DC ± 5%
12WZS 24/500	B 322-X-X	24V DC ± 5%	I _{out} = 500mA 24V DC ± 5%


Vstupné napätie	230V/50Hz
Prevádzková teplota	0÷40 °C
Krytie	IP 30
Hmotnosť	690g
Farba krabičky	čierna, biela



š	v	d
71	57	107

Napájacie konektory:

Polarita:



C-5,50x2,10mm
D-5,50x2,50mm
F-5,50x1,50mm



I-5,50x2,10mm
J-5,50x2,50mm
K-5,50x1,50mm